

exceeding 500 feet prior to or upon setting a string of casing, or production liner, and at total depth. Composite directional surveys shall be prepared with the interval shown from the bottom of the conductor casing. In calculating all surveys, a correction from the true north to Universal-Transverse-Mercator-Grid-north or Lambert-Grid-north shall be made after making the magnetic-to-true-north correction. A composite dipmeter directional survey or a composite measurement while-drilling directional survey will be acceptable as fulfilling the applicable requirements of this paragraph.

(4) Wells are classified as vertical if the calculated average of inclination readings weighted by the respective interval lengths between readings from surface to drilled depth does not exceed 3 degrees from the vertical. When the calculated average inclination readings weighted by the length of the respective interval between readings from the surface to drilled depth exceeds 3 degrees, the well is classified as directional.

(5) At the request of a holder of an adjoining lease, the Regional Supervisor may, for the protection of correlative rights, furnish a copy of the directional survey to that leaseholder.

(f) *Fixed drilling platforms.* Applications for installation of fixed drilling platforms or structures including artificial islands shall be submitted in accordance with the provisions of subpart I, Platforms and Structures, of this part. Mobile drilling units that have their jacking equipment removed or have been otherwise immobilized are classified as fixed bottom founded drilling platforms.

(g) *Crane operations.* You must operate a crane installed on fixed platforms according to § 250.108 of this subpart.

(h) *Diesel-engine air intakes.* After August 14, 1992, diesel-engine air intakes shall be equipped with a device to shut down the diesel engine in the event of runaway. Diesel engines that are continuously attended shall be equipped with either remote-operated manual or automatic-shutdown devices. Diesel engines that are not continuously at-

tended shall be equipped with automatic shutdown devices.

[56 FR 32100, July 15, 1991, as amended at 58 FR 49928, Sept. 24, 1993. Redesignated and amended at 63 FR 29479, 29487, May 29, 1998; 63 FR 34597, June 25, 1998; 65 FR 15864, Mar. 24, 2000]

#### § 250.1606 Control of wells.

The lessee shall take necessary precautions to keep its wells under control at all times. Operations shall be conducted in a safe and workmanlike manner. The lessee shall utilize the best available and safest drilling technologies and state-of-the-art methods to evaluate and minimize the potential for a well to flow or kick. The lessee shall utilize personnel who are trained and competent and shall utilize and maintain equipment and materials necessary to assure the safety and protection of personnel, equipment, natural resources, and the environment.

#### § 250.1607 Field rules.

When geological and engineering information in a field enables a District Supervisor to determine specific operating requirements, field rules may be established for drilling, well completion, or well workover on the District Supervisor's initiative or in response to a request from a lessee; such rules may modify the specific requirements of this subpart. After field rules have been established, operations in the field shall be conducted in accordance with such rules and other requirements of this subpart. Field rules may be amended or canceled for cause at any time upon the initiative of the District Supervisor or upon the request of a lessee.

#### § 250.1608 Well casing and cementing.

(a) *General requirements.* (1) For the purpose of this subpart, the several casing strings in order of normal installation are:

- (i) Drive or structural,
- (ii) Conductor,
- (iii) Cap rock casing,
- (iv) Bobtail cap rock casing (required when the cap rock casing does not penetrate into the cap rock),
- (v) Second cap rock casing (brine wells), and
- (vi) Production liner.